



All Purpose Neutralizer



Ideal for use on VCT and Hard Floor surfaces, **Pioneer Eclipse All Purpose Neutralizer** improves coating adhesion on alkaline surfaces. This product is excellent for use after stripping processes and during winter months to remove salt build up.

DIRECTIONS

Read all directions and Safety Data Sheets (SDS) before using.

Neutralizing Floor After Stripping

1. For hard floors, dilute product at 1:10 (13 US oz per gallon of water or 500 ml per 5 liters of water).
For vinyl floors, dilute at 1:64 (2 US oz per gallon of water or 80 ml per 5 liters of water).
2. Apply with mop or automatic scrubber to neutralize.
3. Allow to soak for 10 minutes, rinse with water and allow to dry thoroughly before applying sealer and/or coating.

Removing Salt Films

1. Clean floors to remove soil residues.
2. For moderate salt films, dilute at 1:128 (1 US oz per gallon or 40 ml per 5 liters of water) in mop bucket or automatic scrubber.
For heavy salt films, dilute at 1:64 (2 US oz per gallon of water or 80 ml per 5 liters of water).
3. Pick up solution and allow floor to dry thoroughly before burnishing.

PRODUCT INFO

Product Code 347MP

Volume 1 US Gallon

Shipping Packaging 4 x 1 gallons

SURFACES



VCT

TERRAZZO

CONCRETE

MARBLE

QUARRY
TILE

TECHNICAL DATA

Description All purpose neutralizer

Appearance Cleaner, colorless liquid

Viscosity (Brookfield) <10 centipoise

VOC 0.08% (as supplied) <0.01 (1:10) (1:64)
40 CFR Part 59 Subpart D

pH 2.2 (as supplied)
ASTM D2834-95

Non-volatile solids 22%
ASTM E70-07 (2008)

Fragrance None added

Shelf Life 2 years
ASTM D1791-93 (2008)

Density 8.7 lb/gal
ASTM D1475-13 (2008)

Container 1 US Gallon

