

HARD FLOORS

EnviroStar[™]

ALL PURPOSE NEUTRALIZER

Neutralizer that improves coating adhesion, especially where alkalinity is a problem.



WHY ENVIROSTAR ALL PURPOSE NEUTRALIZER:

REMOVES SALT FILM

Mild acid solution

REDUCES FLOOR ALKALINITY, IMPROVES COATING ADHESION

EVEN COVERAGE

Surfactant additive

ENVIRONMENTALLY PREFERRED

TECHNICAL DATA

Description	All purpose neutralizer
Appearance	Clear colorless
pH ASTM E70-07	2.2 (as supplied)
Viscosity (Brookfield) (a 68°F (20°C)	<10 centipoise
Fragrance	None added
Shelf Life ASTM D1791-93 (2015)	2 years
Density ASTM D1475-98 (2008)	8.7 lb/gal @ 68°F 1.05 kg/L @ 20°C
VOC 40 CFR Part 59 Subpart C	0.08% (as supplied) <0.01 (1:10) <0.01 (1:64)

DIRECTIONS

Dilute with water at 1:10. Apply with mop or automatic scrubber to neutralize hard floors.

Allow to soak for 10 minutes.

Rinse with water and allow to dry.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com





Product Code
Volume
Shipping Package
Pallet Quantity

338MPE 4 liters 4 x 4 liters 48

338_PDS 02/