



Eclipse™

ANTI-SLIP TREATMENT

An indoor/outdoor anti-slip floor treatment formulated to make smooth and/or wet surfaces less slippery.

WHY ECLIPSE ANTI-SLIP TREATMENT:

INCREASES THE CO-EFFICIENT OF FRICTION TO REDUCE THE POTENTIAL FOR SLIPS AND FALLS

INDOOR AND OUTDOOR USE

NO CHANGE IN APPEARANCE OF SURFACE WHEN USED CORRECTLY

DIRECTIONS

Biodegradable, suitable for indoor and outdoor use.

Read all directions and Safety Data Sheets (SDS) before using.

Detailed directions and SDS sheets are available for download at pioneereclipse.com



TECHNICAL DATA

Description	Anti-Slip / surface modifier Ready to use
Appearance	Clear colorless
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise
Flash Point ASTM D56-05 (2010)	>200°F (93°C)
Coverage Rate*	50 to 250 ft ² /gal 4 to 7 m ² /liter
Dry Time	10 - 15 minutes
VOC 40 CFR Part 59 Subpart C	0.02%
Fragrance	Mild odor
Shelf Life ASTM D1791-93 (2008)	2 years
Density ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.03 kg/L @ 20°C
Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

*Coverage is approximate and may vary depending on surface finish/texture, concrete condition, climatic conditions, etc.

SURFACES



Product Code	427MPE
Volume	4 liters
Shipping Package	4 x 4 liters
Pallet Quantity	48